			Title		
			Lithium ion Rechargeable Cell Specification (SPB58253172V3)		
	RESPONSIBLE	DATE	SIZE	DOCUMENT NO.	REV
AUTHORS			A4	CE16-5020	00
USER					
RELEASE			MANUAL CHANGE PROHIBITED		SHEET 1 OF 3

Lithium ion Rechargeable Cell Specification




SPB58253172V3, 3.7V, 25.0Ah

Enertech International, Inc.

269, Chungjuhosu-ro, Chungju-si, Chungcheongbuk-do, Korea

TEL: 82-43-850-1803 FAX: 82-43-855-9172

<http://www.enertechint.com>

Enertech International, Inc.	Issued 	Checked 	Approved 

CONFIDENTIAL / SENSITIVE INFORMATION

Note: This document and any attachments may be proprietary, privileged and confidential, or otherwise protected from disclosure. If the reader of this document is not the intended recipient, or an employee or agent responsible for delivering this document to the intended recipient, you are hereby notified that you are not authorized to read, print, retain or copy this document or any part of it, and that any dissemination or distribution of this message is strictly prohibited. If you have received this document in error, please notify the person who delivered it immediately and destroy all copies of this document.

TITLE	SIZE	DOCUMENT NO.	REV
Battery Specification (SPB58253172V3)	A4	CE16-5020	00
	MANUAL CHANGE PROHIBITED		SHEET 2 OF 3

1. Descriptions

1.1 Description	Rechargeable Lithium ion Rechargeable Cell
1.2 Model	SPB58253172V3

2. Nominal specification

Item	Specification	
2.1 Nominal Capacity	25.0h (0.3C discharge)	
2.2 Energy density	Volumetric	366Wh/L
	Gravimetric	193Wh/Kg
2.3 Nominal Voltage	3.7V	
2.4 Operating Voltage Range	2.70V ~ 4.20V	
2.5 Standard	Charge Current	8.33A (0.3C)
	Discharge Current	8.33A (0.3C)
2.6 Maximum*	Charge Current	50.0A (2.0C)
	Discharge Current	75.0A (3.0C)
	Peak Discharge	125.0A (5.0C)
2.7 Operating Temperature	Charge	0°C ~ 55°C
	Discharge	-20°C ~ 55°C
	Recommend	25 ± 3°C
2.8 Storage Temperature	-20°C ~ 25°C	≤ 1Year
	-20°C ~ 55°C	≤ 1Month
2.9 Storage Humidity	45 ~ 85%RH	
2.10 Cell size	Thickness	5.8 +0.2/-0.4mm (Initial fully charged Cell)
	Width	253.0 ± 1.0mm
	Length	172.0 ± 1.0mm
2.11 AC Impedance	Max. 2.0mΩ	
2.12 Weight	Max. 480.0g	

* Maximum Current is not for the continuous cycle condition, only check the cell performance.

TITLE	SIZE	DOCUMENT NO.	REV
Battery Specification (SPB58253172V3)	A4	CE16-5020	00
	MANUAL CHANGE PROHIBITED		SHEET 3 OF 3

3. Mechanical Drawings




Figure 1 Lithium ion Rechargeable Cell Outline Drawing